



OLYMPIC 3

- FLAT SPONGE RUBBER
- SUITABLE FOR USE UNDER LAMINATE AND SOLID WOODEN FLOORS
- CAN BE USED AS A VERY HEAVY CONTRACT CARPET UNDERLAY
- CAN BE USED WITH UNDERFLOOR HEATING



RECOMMENDED AREAS OF USE

SUITABLE FOR DOMESTIC AND CONTRACT APPLICATIONS. FOR USE WITH LAMINATE, SOLID AND ENGINEERED WOOD INSTALLATIONS.

Manufactured in the UK to BS EN 14499:2015

STANDARD SPECIFICATIONS		
TOP SURFACE	Stitch bonded perforated crepe paper	
BOTTOM SURFACE	Spun bonded non-woven fabric	
NOMINAL THICKNESS	3.00 mm	
NOMINAL ROLL WEIGHT	33.0 kg	72.7 lb
WEIGHT PER UNIT AREA	2190 g/m ²	65 oz/yd ²
ROLL LENGTH	11.0 m	36.0 ft
ROLL WIDTH	1.37 m	54 in
GUARANTEE	Lifetime of the floor covering (when used in recommended areas)	

BS EN 14499:2015 TEST RESULTS - UK and EU STANDARD FOR CARPET UNDERLAYS		
END USE CLASSIFICATION	BS EN 14499	N/A
WORK OF COMPRESSION AFTER 1000 IMPACTS	BS 4098	N/A
RETENTION OF WORK OF COMPRESSION	BS 4098	N/A
LOSS IN THICKNESS AFTER STATIC LOADING	BS 4939 ISO 3416	<5.00 %
LOSS IN THICKNESS AFTER DYNAMIC LOADING	BS ISO 2094 (R05)	<5.00 %
RESISTANCE TO CRACKING	BS EN 14499	Pass

FIRE RESISTANCE TESTS		
EUROPEAN REACTION TO FIRE CLASSIFICATION	EN13501-1	CFL-s1
NBS RADIANT PANEL	ASTM E648	Pass-Category 1

INDOOR AIR QUALITY TEST		
TESTED TO ISO16000		
EUROFINS INDOOR AIR COMFORT ® STANDARD		Pass
EUROFINS INDOOR AIR COMFORT GOLD ® STANDARD		Pass
FRENCH VOC REGULATIONS		A+
FRENCH CMR COMPONENTS		Pass
ITALIAN CAM		Pass
AgBB/ABG		Pass
FORMALDEHYDE EMISSION CLASS		E1
BREEAM INTERNATIONAL		Compliant
LEED v4 (Outside U.S.)		Compliant
BREEAM ® NOR		Compliant



OTHER RELEVANT TESTS		
THERMAL RESISTANCE (TOG RATING)	BS 4745	0.3 TOG
IMPACT SOUND IMPROVEMENT INDEX (Test/Rated)	BS EN ISO 10140-3 BS EN ISO 717-2)	19 dB

ISSUE 4 21-OCT-20